

Sonus SBC 5100™ Session Border Controller

For years, the world's largest service providers and enterprises have relied on Sonus session border controllers (SBCs) for secure SIP-based communications. The SBC 5100 delivers many of the industry-leading capabilities of the Sonus SBC 5200—robust security, flexible SIP session routing & policy management, media transcoding—at a more attractive price/performance point for Tier 2/3 service providers and medium-to-large enterprises (250 to 10,000 concurrent sessions). With high-end features you won't find in other “mid-sized” SBCs, the SBC 5100 allows regional service providers and medium-to-large enterprises to deliver a world-class communications experience designed for their world. The SBC 5100 Series is available in two form factors: modular (SBC 5110) and fixed (SBC 5100). The SBC 5100 Series delivers true multimedia SBC support for audio, video and collaboration with advanced security, priority, identity and service quality capabilities.



System Capabilities

- Sessions
 - 10,000 sessions (SIP and/or H.323)
 - 10,000 calls
 - 10,000 transcoded sessions (based upon codec type)
 - RTCP sessions scale 1:1 with RTP sessions
- Call Set-Up
 - Maximum call setup rate: 150 cps
- Registrations
 - Maximum new registrations/sec: 400
 - Maximum refreshes/sec: 1,700 per second
 - Total registered end point support: 100,000; up to 10,000 NAT'd end points
- Encryption
 - Maximum number of TLS sessions: 10,000
 - TLS set-up rate: 50 cps w/o mutual authentication
 - Maximum # of IPsec tunnels: 2,048 (4,096 IPsec SAs)
 - IPsec (IKE) setup rate: 50 cps
 - Maximum # SRTP sessions: 10,000

Media Services

- Transcoding up to 10,000 concurrent calls: G.711, G.726, G.728, G.729A/B, G.723, iLBC, G.722, G.722.1, AMR-NB, AMR-WB, EVRCB0, EVRC0
- Wireline, wireless, wideband and clear channel codec pass through
- T.38 compliant fax relay or fall back to G.711
- VAD, Silence Suppression, Dynamic Jitter Buffer, Fax/ Modem Detection, DTMF/Tone Relay/RFC2833/RFC4733 interworking
- NAT/NAPT on media
- DTMF Trigger Detection and Notification
- Generic audio codec relay
- Tones & Announcements
- Local Ring Back Tone (LRBT) support with centralized PSX Policy Server
- RTP inactivity monitoring
- Supported video codecs: H.264 AVC, H.264 SVC, H.263+; H.263, H.261, VP8

Redundancy

- 1:1 Redundant Systems for Service Availability
- 1:1 Redundant Management/ Control Ports

Management Capabilities

- Graphical based wizards for ease of configuration
- Secure embedded web-based management GUI
- Sonus CLI, SSH
- Centralized support by Sonus Insight EMS
- SNMP V2/V3 status and statistics
- Local logging of events, alarms, and traps; Call trace
- Sonus DSI Level 0 support for storing CDRs; RADIUS accounting records
- Live Software Update (LSWU)

Signaling

- Back to Back User Agent (B2BUA)
- SIP, SIP-I/SIP-T, SIP/H.323; Sonus Gateway to Gateway Signaling
- SIP protocol normalization/protocol repair; SIP message manipulation
- NAT/NAPT on signaling
- Binary floor control protocol (BFCP) Far-end camera control (FECC)

Protocol Support

- IPv4, IPv6, IPv4/IPv6 interworking
- SSH; sFTP
- SNMP; NETCONF; NTP
- HTTP/HTTPS
- RTP/RTCP
- UDP, TCP
- DNS, ENUM

Routing/Policy

- Embedded policy/routing engine
- Optional centralized policy/routing via Sonus Centralized Policy Server (PSX Server) using Diameter+
- Screening, blocking, routing, presentation, call type filters
- Route prioritization
- Leading digit routing; International routing; URI based routing
- Digit/parameter manipulation
- E911 support; Priority Call handling

Security

- Session-aware firewall; Topology hiding
- Line rate DoS/DDoS and Rogue RTP protection
- Line rate malformed packet protection
- TLS, IPsec (IKEV1) for signaling encryption
- Secure RTP/RTCP for media encryption

Quality of Service (QoS)

- Bandwidth management
- Call admission control (CAC) per trunk group, per zone
- Per call statistics
- TOS/COS packet marking

Packet Network Time Source

- Network Time Protocol (NTP) per RFC-1708

Hardware Specifications

Front Panel

- Status Indicators Front Panel LEDs
 - Status
 - Critical
 - Major
 - Minor
 - User
 - Location
- Single USB V2.0 interface

Rear Panel

- Management Ports
 - Two (single active, single passive) 10/100/1000 Ethernet RJ-45 ports
- Media Ports
 - Two 1 Gbps Ethernet fiber or copper via SFP
- High Availability Ports
 - Two 1 Gbps Ethernet multimode fiber via SFP
- Single Field Service port with RJ45 connector
- Locator LED
- Alarm port with DB15 connector
- Single serial craft DB9 port

Memory

- 12 GB of RAM

DSP Expansion

- Model 5110: Modular DSP slots
- Model 5100: Fixed DSP cards

Chassis

- 2U, rack mount
- Inches: 17.5" Wide x 3.5" High x 21" Deep
- Centimeters: 44.5 Wide x 8.8 High x 53.3 Deep
- Optional mounting brackets for 19" or 23" rack

Chassis Mounting Options:

- 19" or 23" Adjustable Brackets

Storage

- SBC 5100: 80 GB of Solid State Disk (SSD) storage
- SBC 5110: 128 GB of SSD storage

AC Power Option

- RMS Input Voltage
 - Minimum 90 VAC
 - Nominal 100-240 VAC
 - Maximum 264 VAC

- RMS Current
 - Low Line: 7.1A
 - High Line: 3.4A
- Input Frequency
 - Minimum: 47 Hz
 - Nominal: 50/60 Hz
 - Maximum: 63 Hz

DC Power Option

- SBC 5100
 - Peak Consumption: 14.5A
 - Number of power supplies, standard: 1
 - (Redundant dual power supply optional)
 - SBC 5110
 - Peak Consumption: 16.8A
 - Number of power supplies, standard: 1
- (Redundant dual power supply optional)

Operating Altitude

- 6,000 ft. (1,800 m.)

Heat Dissipation

- Fully-Populated Maximum:
 - 633 Watts
 - 2159 BTU per Hour
- Replaceable Filter

Weight Maximum Fully Populated

- 50 lbs. (22.68 kg)

Environmental

- 5 to 40° C Operating
- -5 to 55° C Short Term
- 5 to 90% Non-Condensing Operating Humidity

Regulatory Compliance

Central Office Standards

- DC Systems – SR-3580 NEBS Level 3
 - GR-1089-CORE
 - GR-63-CORE
- AC Systems – SR-3580 NEBS Level 3
 - GR-1089-CORE
 - GR-63-CORE

Table 1. Estimated Power Consumption (power estimates with fans running at high speed)

Configuration	AC Low Line (W)		AC High Line (W)		DC Input (W)	
	Amps	Watts	Amps	Watts	Amps	Watts
SBC 5110	4.5	408	2.3	407	9.8	390
SBC 5110 +1 DSP25	5.2	472	2.6	465	11.4	454
SBC 5110 +2 DSP25	5.9	530	2.9	525	12.8	512
SBC 5110 +3 DSP25	6.6	597	3.3	591	15.1	604
SBC 5110 +4 DSP25	7.4	667	3.6	654	16.8	673

SBC 5100	SPS100	SPS100DB	AC Low Line		AC High Line		DC	
			Amps	Watts	Amps	Watts	Amps	Watts
	0	0	5.8	515	2.8	502	12.4	519
	1	0	6.7	604	3.3	595	14.8	589
	1	1	7.6	676	3.7	656	16.8	672
	1	2	8.5	755	4.1	731	18.8	751

**Sonus Networks
North American
Headquarters**

4 Technology Park Drive
Westford, MA 01886
U.S.A.
Tel: +1-855-GO-SONUS

**Sonus Networks
APAC
Headquarters**

1 Fullerton Road #02-01
One Fullerton
Singapore 049213
Singapore
Tel: +65 6832 5589

**Sonus Networks
Limited EMEA
Headquarters**

Edison House, Edison Road
Dorcan, Swindon,
Wiltshire SN3 5JX
United Kingdom
Tel: +44 1793 601400

**Sonus Networks
CALA
Headquarters**

Mexico City, Campos
Eliseos Polanco
Andrés Bello 10, Pisos
6 y 7, Torre Forum
Col. Chapultepec Morales,
Ciudad de México
Mexico City, 11560 Mexico
Tel: +52 55 36010600

To learn more, call Sonus at 855-GO-SONUS or visit us online at www.sonus.net

Microsoft Partner
Gold Communications

Voice Unified Communications
Business Productivity Solutions
Midmarket Solution Provider

The content in this document is for informational purposes only and is subject to change by Sonus Networks without notice. While reasonable efforts have been made in the preparation of this publication to assure its accuracy, Sonus Networks assumes no liability resulting from technical or editorial errors or omissions, or for any damages resulting from the use of this information. Unless specifically included in a written agreement with Sonus Networks, Sonus Networks has no obligation to develop or deliver any future release or upgrade or any feature, enhancement or function.

Copyright © 2013 Sonus Networks, Inc. All rights reserved. Sonus is a registered trademark of Sonus Networks, Inc. All other trademarks, service marks, registered trademarks or registered service marks may be the property of their respective owners.